

Date : January 18, 2007

ALTECO CHEMICAL PTE LTD

TECHNICAL DATA SHEET

PRODUCT NAME

EPO-PUTTY (UNDERWATER)

PRODUCT DESCRIPTION

EPO-PUTTY (UNDERWATER) is a putty developed for bonding of steel and concrete materials. It is curable under water or salt water. It can also be used for both wet and dry surfaces.

GENERAL PROPERTIES

Appearance	Non-transparent paste
Viscosity (cP at 25 deg C)	Paste
Specific Gravity (at 25 deg C)	(A) 1.81 ± 0.10 (B) 1.80 ± 0.10
Tensile Shear Strength (kgf/cm^2)*	Minimum 130
Curing Time (Hours at 25 deg C)	2.5
Hardness (Shore D)	Minimum 80
Shelf Life (Months)**	12
Mixing Ratio in Weight	(A) 100 (B) 100

NOTE :

* Steel to Steel bonding.

** Shelf life is subjected to change due to the type of packaging used and the condition of the environment.

All testings are conducted at 23 ± 2 deg C unless otherwise specified.

REMARKS :

All information for the use of our product are based on the results of tests carried out by ALTECO. The buyer shall be responsible for satisfying himself that the product is suitable for his intended purpose since we cannot control the application and the use of the product. The buyer is advised to conduct individual tests before the actual application.