


*Welcome to our company!*  
*Welcome to our company!*

[Home](#)   [E-Mail](#)   [Korean](#)

[Company Info.](#)  
[Product Info.](#)  
[Technology](#)  
[Production Line](#)  
[Register](#)  
[Bulletin Board](#)

**Product Information**



**P.E (Polyethylene) Foam tape**

**Physical Properties**

Carrier	Item no.	Thickness (mm)	Line
	398E	1.0	Red color
<b>Black P.E Foam</b>	390	0.95	Red color
	391	1.50	Red color
	398EW	1.0	Red color
<b>White P.E Foam</b>	390W	0.95	Red color

**Performance Characteristics**

Carrier	Item no.	Adhesion (gf/10mm)	Tensile strength (kgf/cm <sup>2</sup> )
<b>Black P.E Foam</b>	398E	1000	5.0
	390	900	5.7
	391	900	5.5
<b>White P.E Foam</b>	398EW	1000	5.0
	390W	900	5.7

**Note** : All products manufactured by BOW TAPE are guaranteed to be free from defect at the time of shipping when tested according to BOW TAPE products specifications. The above figures are average

**BOW TAPE**

- Homepage : <http://www.bowtape.co.kr/>
- Company : BOW TAPE CO.,LTD
- Phone : 82-31-353-6780
- FAX : 82-31-353-6787
- Address : #498 Kyehyang-Li, Jeingnam-Myun, Hwasung-City, Kyunggi-I Code : 445-961)
- URL : (1)<http://www.bowtape.co.kr/>

E-mail : (2)<http://www.bowtape.com/>  
<mailto:bowtape@bowtape.co.kr?bcc=webmaster@smipc.or.kr>