



BRICOFIX WALLPAPER

DATA SHEET
06/2019



DESCRIPTION:

Adhesive based on cellulosic derivatives.

APPLICATIONS:

Preparation of surfaces before attaching paper. Especially suitable for positioning and pasting wallpaper.

INSTRUCTIONS:

Pour the powder on cold water stirring continuously while adding all the powder. Then let stand for a minimum of 15 minutes and stir the mixture again, thus leaving the product ready for use.

Dosage is carried out according to the following table:

USE	DOSAGE	POUR ONE BAG IN
Strong papers...	1:40	5 litres of water
Medium papers	1:50	6 ¼ l. water
Fine papers	1:60	7 ½ l. water
Preparation of walls	1:70	8 ¾ l. water

The adhesive is applied with a brush or roller on the back of the paper to be bonded. Leave for a while to permit thorough moistening.

Then, place the paper strip on the wall, which has to be clean, dry and perfectly prepared.

With the aid of a sponge or brush smooth out the surface, eliminating air bubbles by even pressure applied from the centre to the borders of the paper.

In the joints, it is recommended to press with a rubber roller.

Due to its composition the adhesive is protected from mold and putrefaction.

STORAGE:

At least 3 years in its original sealed packages.

PRESENTATION:

Boxes 125 g

TECHNICAL FEATURES:

Appearance: Fine white granules.

Viscosity: Brookfield RVT. Spindle 4 to 20 rpm
2% water solution at 23°C.

15.000 ± 5.000 cps.

Solution: Transparent.

CLEANING:

The cleaning of the tools must be made with water immediately after using.

HEALTH & SAFETY:

According to current legislation, this product is free of risks and requires no special safety measure when manipulating or storing.

For more information request the Safety Data Sheet.

"The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent.

Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."



Quilosa - Selena Iberia S.L.U.

Centro empresarial Rivas Futura, C/ Marie Curie 19, Planta 6.1, 28521 Rivas, Madrid, Spain,
Tel: +34 902 02 18 02 – Fax: +34 914 999 796, info@quilosa.es, www.quilosa.com