



**WIPE NEW®
CERAMIC TRIM RESTORE**

DESCRIPTION AND USES

Wipe New® Ceramic Trim Restore revives and renews the original color and shine to uncoated exterior vinyl and plastic trim while ceramic protection ensures long lasting durability. The precise aerosol application delivers thorough coverage and minimizes overspray.

PRODUCT FEATURES

- Restores the original color & shine to exterior trim
- Durable ceramic protection prevents future fading and discoloration
- Precision application minimizes overspray
- Fast drying formula, no greasy residue

PRODUCT

DESCRIPTION	SKU
10 oz.	381705

PRODUCT APPLICATION

DIRECTIONS

(Read entire directions and warnings prior to use.)

Shake well before use.

- Prep the surface by thoroughly cleaning and drying the area to be treated. Use in a well ventilated area.
- Be sure surface is cool to the touch and do not apply in direct sunlight.
- Before using, test in a small area first to give you an idea of spray pattern.
- When applying, hold can approximately 6 inches from surface and with a smooth, even motion apply a thin coat of Wipe New Ceramic Trim Restore to the surface. Repeat with a 2nd coat to ensure even coverage. Do not over apply.

Product will dry to the touch in 10 minutes and completely dry in 1 hour.

PHYSICAL PROPERTIES

		CERAMIC TRIM RESTORE
Pigment Type		NA
Fill Weight		10 oz.
Solvents		Methyl Acetate, Mineral Spirits
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	10 minutes
	Handle	30 minutes
	Full Cure	1 hour
Shelf Life		2 years
Flash Point		>200°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

